


FEATURES

- Wide range of supply voltages
- Low supply current drain independent of supply voltage
- Low input biasing current
- Low input offset voltage and offset current
- Input common-mode voltage range includes ground
- Differential input voltage range equal to the power supply voltage
- DC voltage gain 100V/mV Typ.
- Internally frequency compensation

DESCRIPTION

The TJ358 consists of two independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage.

Application areas include transducer amplifiers, DC gain blocks and all the conventional op amp circuits.



ORDERING INFORMATION

Device	Package
TJ358GD	SOP-8
TJ358GTD	TSSOP-8

ABSOLUTE MAXIMUM RATINGS (Note 1)

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Supply Voltage	V_{CC}	-	45 or ± 22.5	V
Differential Input Voltage	V_{ID}	-	45	V
Input Voltage Range (either input)	V_{IC}	-0.3	45	V
Input Current ($V_{ID} = -0.3V$)	I_{IN}	-	50	mA
Maximum Junction Temperature	T_J	-40	125	$^{\circ}C$
Storage Temperature Range	T_{STG}	-65	150	$^{\circ}C$

Note 1. Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS (Note 2)


CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Supply Voltage ([VCC+] – [VCC-])	V _{CC}	5	40	V
Input Voltage Range (either input)	V _{IC}	-	40	V
Operating Ambient Temperature Range	T _{OPR}	-40	125	°C

Note 2. The device is not guaranteed to function outside its operating ratings.

ORDERING INFORMATION

Package	Order No.	Description	Supplied As	Status
SOP-8	TJ358GD	Dual Operational Amplifiers	Tape & Reel	Active
TSSOP-8	TJ358GTD	Dual Operational Amplifiers	Tape & Reel	Active

PIN CONFIGURATION



SOP-8 / TSSOP-8

PIN DESCRIPTION

Pin No.	Pin Name	Pin Function
1	OUT1	Output of the Amplifier 1
2	IN1(-)	Inverting Input of the Amplifier 1
3	IN1(+)	Non-inverting Input of the Amplifier 1
4	GND	Ground or Negative Supply (VCC-)
5	IN2(+)	Non-inverting Input of the Amplifier 2
6	IN2(-)	Inverting Input of the Amplifier 2
7	OUT2	Output of the Amplifier 2
8	VCC	Positive Power Supply (VCC+)

ELECTRICAL CHARACTERISTICS

At specified free-air temperature, $V_{CC} = 5V$, unless otherwise specified

SYMBOL	PARAMETER	TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
V_{IO}	Input Offset Voltage	$V_{CC} = 5V$ to MAX, $V_{IC} = V_{ICR}$ min, $V_O = 1.4V$	25°C	-	3	7	mV
			Full range	-	-	9	
αV_{IO}	Average Temperature Coefficient of Input Offset Voltage		Full range	-	7	-	$\mu V/^\circ C$
I_{IO}	Input Offset Current	$V_O = 1.4V$	25°C	-	2	50	nA
			Full range	-	-	150	
αI_{IO}	Average Temperature Coefficient of Input Offset Current		Full range	-	10	-	$\mu A/^\circ C$
I_{IB}	Input Bias Current	$V_O = 1.4V$	25°C	-	-20	-250	nA
			Full range	-	-	-500	
V_{ICR}	Common-mode Input Voltage Range	$V_{CC} = 5V$ to MAX	25°C	0	-	$V_{CC}-1.5$	V
			Full range	0	-	$V_{CC}-2.0$	
V_{OH}	High-Level Output Voltage	$V_{CC} = MAX$, $R_L = 2k\Omega$	Full range	26	-	-	V
		$V_{CC} = MAX$, $R_L \geq 10k\Omega$	Full range	27	28	-	
V_{OL}	Low-Level Output Voltage	$R_L \geq 10k\Omega$	Full range	-	5	20	mV
A_{VD}	Large-Signal Differential Voltage Amplification	$V_{CC} = 15V$, $V_O = 1V$ to $11V$, $R_L \geq 2k\Omega$	25°C	25	100	-	V/mV
			Full range	15	-	-	
CMRR	Common-mode Rejection Ratio	$V_{CC} = 5V$ to MAX, $V_{IC} = V_{ICR}$ min	25°C	65	80	-	dB
PSRR	Supply Voltage Rejection Ratio ($\Delta V_{CC}/\Delta V_{IO}$)	$V_{CC} = 5V$ to MAX	25°C	65	100	-	dB
V_{O1}/V_{O2}	Crosstalk Attenuation	$f = 1kHz$ to $20kHz$	25°C	-	120	-	dB
I_{O+}	Output Source Current	$V_{CC} = 15V$, $V_{ID} = 1V$, $V_O = 0V$	25°C	-30	-50	-	mA
			Full range	-20	-	-	
I_{O-}	Output Sink Current	$V_{CC} = 15V$, $V_{ID} = -1V$, $V_O = 15V$	25°C	15	35	-	mA
			Full range	7	-	-	
		$V_{ID} = -1V$, $V_O = 2V$	25°C	15	28	-	mA
			25°C	12	50	-	
I_{SC}	Output Short-Circuit Current	$V_{ID} = -1V$, $V_O = 0V$	25°C	-	50	70	mA
I_{CC}	Supply Current	$V_{CC} = 2.5V$, No Load	Full range	-	0.7	1.2	mA
		$V_{CC} = MAX$, $V_O = 0.5V_{CC}$, No Load	Full range	-	1	2	


ELECTRICAL CHARACTERISTICS (continued)

SYMBOL	PARAMETER	TEST CONDITIONS	T _A	MIN	TYP	MAX	UNIT
SR	Slew Rate	V _{CC} = 15V, V _{IN} = 0.5V to 3V, R _L = 2kΩ, C _L = 100pF, Unity Gain	25°C	-	0.7	-	V/μs
GBW	Gain Bandwidth	V _{CC} = MAX, f = 100kHz, V _{IN} = 10mV, R _L = 2kΩ, C _L = 100pF	25°C	-	700	-	kHz
THD	Total Harmonic Distortion	f = 1kHz, A _V = 20dB, R _L = 2kΩ, V _O = 2Vpp, C _L = 100pF	25°C	-	0.04	-	%


Note 3. Temperature full range is -40°C to +125°C. V_{CC} MAX for testing purpose is 36V.

Note 4. All characteristics are measure under open loop conditions with zero common-mode input voltage unless otherwise specified.


TYPICAL OPERATING CHARACTERISTICS




Supply current vs. Supply voltage




Current Sourcing vs. Output Characteristics




Voltage Follower Pulse Response



Current Sinking vs. Output Characteristics



Voltage Follower Pulse Response (Small Signal)



Open Loop Frequency Response

REVISION NOTICE

The description in this datasheet is subject to change without any notice to describe its electrical characteristics properly.